

125Lb.Flanged

CAST IRON VALVE

Fig No.	1	
Material	Body	A 126 Class B
	Trim	C83600
Standard	ASME	
Working Pressure	<ul style="list-style-type: none"> • 2" ~ 12" / 200PSI-WOG(100°F) 125PSI-Saturated Steam • 14" ~ 24" / 150PSI-WOG(100°F) 125PSI-Saturated Steam 	

Appearance



Dimension		L	H	W
1 1/2 inch	40 mm			
2	50	178	245	158
2 1/2	65	190	272	158
3	80	203	297	158
4	100	229	355	195
5	125	254	397	195
6	150	267	465	220
8	200	292	561	280
10	250	330	669	310
12	300	356	778	355
14	350	381	904	450
16	400	406	1039	500
18	450	432	1151	560
20	500	457	1264	630
24	600	508	1473	710

Remark



☎ +63-939-913-0553,
+63-917-850-4147
☎ Fax: +63(2)8244-1234
Tel.: +63(2)8244-7061 to 68

For Inquiries:
✉ sales10@upcc.com.ph
For Concerns:
✉ inquiry@upcc.com.ph

📍 7th floor, Banawe Lifestyle Center Building, 86 Banawe St., Brgy. Sto. Domingo, Quezon City, Philippines