

CAP


Bouchon femelle

For dimensions B-J refer to dimensions of S.W. fittings

Dimensions B-J, voir caractéristiques dimensionnelles

Class 3000 lbs. - 6000 lbs.

Socket welding end and dimensions according to ASME: B16.11



Nominal pipe size Diamètre nominal	3000				6000			
	O ⁽¹⁾		p ⁽¹⁾		O ⁽¹⁾		p ⁽¹⁾	
	inches	mm	inches	mm	inches	mm	inches	mm
1/4	0.79	20	0.87	22	0.79	20	0.90	26
3/8	0.79	20	1.02	26	0.79	20	1.10	28
1/2	0.79	20	1.26	32	0.87	22	1.38	35
3/4	0.94	24	1.50	38	0.98	25	1.57	45
1	1.06	27	1.77	45	1.10	28	1.97	50
1 1/4	1.06	27	2.17	55	1.10	28	2.36	60
1 1/2	1.10	28	2.48	63	1.18	30	2.64	67
2	1.30	33	2.95	75	1.42	36	3.35	85
2 1/2	1.42	36	3.62	95	1.53	39	3.94	100
3	1.57	40	4.33	110	1.73	44	4.72	120
4	1.77	45	5.51	140	2.01	51	5.91	150

⁽¹⁾ Dimensions not listed in ASME B 16.11 and BS 3799 may vary according to the manufacturer.

⁽¹⁾ Dimensions non reprises dans ASME B 16.11 ET BS 3799, pouvant varier selon le fabricant.