

125Lb.Flanged

Fig No.		6		
Material	Body	A 126B		
	Trim	C83600 or F6		
Standard		ASME		
Working Pressure		<ul style="list-style-type: none"> ● 2"~12"/200PSI-WOG(100°F) 125PSI-Saturated Steam ● 14"~24"/150PSI-WOG(100°F) 125PSI-Saturated Steam 		
Appearance				
Dimension		L	H(Open)	W
1 1/2 inch	40 mm			
2	50	178	308	160
2 1/2	65	190	358	180
3	80	203	404	180
4	100	229	498	224
5	125	254	588	224
6	150	267	708	250
8	200	292	918	280
10	250	330	1120	300
12	300	356	1312	355
14	350	381	1539	450
16	400	406	1793	500
18	450	432	1995	560
20	500	457	2194	600
24	600	508	2670	710
Remark				



 +63-939-913-0553,
 +63-917-850-4147
 Fax: +63(2)8244-1234
 Tel.: +63(2)8244-7061 to 68

For Inquiries:
 sales10@upcc.com.ph
 For Concerns:
 inquiry@upcc.com.ph

 7th floor, Banawe Lifestyle
 Center Building, 86 Banawe
 St., Brgy. Sto. Domingo,
 Quezon City, Philippines