


## Screwed (PT or NPT)

Fig No.	56		
Item	150-Y.Strainer		
Material	※1 Bronze		
Class	150Lb.	16K	25bar
Connection	NPT	PT	
Standard	ASME	JIS	BS
Working Pressure	<ul style="list-style-type: none"> <li>● JIS/ 1.96MPa(-10~120°C)</li> <li>● BS/25bar(-10~100°C)</li> <li>● ASME/300PSI-WOG(100°F)</li> </ul>		

## Appearance



Dimension		L	H
1/4 inch	8mm		
3/8	10	70	44
1/2	15	80	49
3/4	20	100	57
1	25	115	72
1 1/4	32	135	82
1 1/2	40	160	98
2	50	195	121
2 1/2	65	230	150
3	80	239	180
4	100		

※1 Bronze Material

Standard	Designation
ASTM	C83600
JIS	CAC406
BS	EN1982 CC491K



☎ +63-939-913-0553,  
+63-917-850-4147  
☎ Fax: +63(2)8244-1234  
☎ Tel.: +63(2)8244-7061 to 68

For Inquiries:  
✉ sales10@upcc.com.ph  
For Concerns:  
✉ inquiry@upcc.com.ph

📍 7th floor, Banawe Lifestyle  
Center Building, 86 Banawe  
St., Brgy. Sto. Domingo,  
Quezon City, Philippines