


ASME 45°エルボ (ロング) の形状・寸法・重量 / DIMENSIONS OF LONG RADIUS ELBOW



45° LONG RADIUS ELBOW



ASME B 16.9

Nominal Pipe Size (NPS)	Dimensions (Unit:mm)		Carbon & Alloy Steel Weight (Unit:kg)														Stainless Steel Weight (Unit:kg)			
	Outside Diameter at Bevel	Center - to - End 45 Deg Elbow																		
			D	B	STD	XS	XXS	S40	S80	S120	S160	S10	S20	S30	S60	S100	S140	S10S	S40S	S80S
1/2	21.3	16	0.038	0.048	0.076	0.038	0.048	-	0.058	-	-	-	-	-	-	0.030	0.040	0.050	0.060	
3/4	26.7	19	0.060	0.077	0.131	0.060	0.077	-	0.115	-	-	-	-	-	-	0.050	0.062	0.080	0.115	
1	33.4	22	0.106	0.137	0.231	0.106	0.137	-	0.180	-	-	-	-	-	-	0.070	0.107	0.140	0.180	
1-1/4	42.2	25	0.163	0.215	0.374	0.163	0.215	-	0.270	-	-	-	-	-	-	0.110	0.167	0.220	0.270	
1-1/2	48.3	29	0.218	0.292	0.515	0.218	0.292	-	0.390	-	-	-	-	-	-	0.160	0.220	0.295	0.395	
2	60.3	35	0.361	0.497	0.893	0.361	0.497	0.560	0.736	-	-	-	-	-	-	0.260	0.365	0.510	0.750	
2-1/2	73.0	44	0.728	0.961	1.720	0.728	0.961	0.740	1.260	-	-	-	-	-	-	0.420	0.735	0.970	1.270	
3	88.9	51	1.090	1.470	2.670	1.090	1.470	1.455	2.060	-	-	-	-	-	-	0.660	1.100	1.490	2.090	
3-1/2	101.6	57	1.470	2.020	3.690	1.470	2.020	-	3.020	-	-	-	-	-	-	0.820	1.510	2.050	3.050	
4	114.3	64	1.940	2.690	4.940	1.940	2.690	3.380	4.040	-	-	-	-	-	-	1.100	2.040	2.710	4.080	
5	141.3	79	3.270	4.650	8.630	3.270	4.650	6.000	7.380	-	-	-	-	-	-	2.010	3.460	4.690	7.450	
6	168.3	95	5.100	7.690	14.30	5.100	7.690	9.720	12.20	-	-	-	-	-	-	2.950	5.740	7.770	12.30	
8	219.1	127	10.20	15.60	26.00	10.20	15.60	21.70	26.80	-	10.20	10.20	-	-	-	5.150	10.30	15.80	-	
10	273.0	159	18.10	24.50	46.40	18.10	28.80	39.80	51.80	-	18.10	18.10	-	-	-	8.400	18.30	24.60	-	
12	323.8	190	26.70	35.20	67.00	28.80	47.60	67.00	85.50	-	26.70	26.70	39.10	-	-	14.30	26.75	35.35	-	
14	355.6	222	34.20	45.30	-	39.80	66.60	94.10	119.0	34.20	34.20	34.20	53.00	94.10	119.0	18.300	40.20	-	-	
16	406.4	254	44.90	59.40	-	59.40	97.90	137.0	176.0	44.90	44.90	44.90	76.50	137.0	176.0	36.10	60.00	-	-	
18	457.0	286	56.90	75.40	-	84.50	138.0	196.0	249.0	56.90	56.90	75.40	110.0	196.0	249.0	-	-	-	-	
20	508.0	318	70.50	93.40	-	110.0	187.0	264.0	338.0	70.50	70.50	93.40	148.0	264.0	338.0	-	-	-	-	
22	559.0	343	85.00	112.5	-	140.0	246.0	347.0	442.0	85.00	83.70	112.5	-	347.0	442.0	-	-	-	-	
24	610.0	381	102.0	135.0	-	184.0	319.0	459.0	580.0	102.0	102.0	184.0	255.0	459.0	580.0	-	-	-	-	