

OKI

Brochure

OKI®



PRODUCT LINEUP

90° Elbow	Long		Short	
45° Elbow	Long		Short	
Tee	Straight		Reducing	
Reducer	Concentric		Reducing	
Cap	Cap			

CARBON STEEL & GALVANIZED SEAMLESS BUTTWELDING PIPES FITTINGS



STEEL BUTTWELDING FITTINGS

DIMENSION OF WELDING FITTINGS

ANSI B 16.9 & B16.28

Nominal Pipe Size	Outside Diameter	LONG				SHORT	TEES		CAPS	REDUCERS	Nominal Pipe Size
		90° ELBOWS	45° ELBOWS	180° RETURNS		90° ELBOWS	Center to End				
		Center to End	Center to End	Center to Center	Back to Face	Center to End	Run	※1 Outlet	※2 Back to Face	End to End	
D	O.D.	A	B	P	K	A	C	M	E	H	D
1/2	0.84	1.50	0.62	3.00	1.88	-	1.00	1.00	1.00	-	0.84
3/4	1.05	1.12	0.44	2.25	1.69	-	1.12	1.12	1.00	1.50	1.05
1	1.32	1.50	0.88	3.00	2.19	1.00	1.50	1.50	1.50	2.00	1
1-1/4	1.66	1.88	1.00	3.75	2.75	1.25	1.88	1.88	1.50	2.00	1-1/4
1-1/2	1.90	2.25	1.12	4.50	3.25	1.50	2.25	2.25	1.50	2.50	1-1/2
2	2.38	3.00	1.38	6.00	4.19	2.00	2.50	2.50	1.50	3.00	2
2-1/2	2.88	3.75	1.75	7.50	5.19	2.50	3.00	3.00	1.50	3.50	2-1/2
3	3.50	4.50	2.00	9.00	6.25	3.00	3.38	3.38	2.00	3.50	3
3-1/2	4.00	5.25	2.25	10.50	7.25	3.50	3.75	3.75	2.50	4.00	3-1/2
4	4.50	6.00	2.50	12.00	8.25	4.00	4.12	4.12	2.50	4.00	4
5	5.56	7.50	3.12	15.00	10.31	5.00	4.88	4.88	3.00	5.00	5
6	6.62	9.00	3.75	18.00	12.31	6.00	5.62	5.62	3.50	5.50	6
8	8.62	12.00	5.00	24.00	16.31	8.00	7.00	7.00	4.00	6.00	8
10	10.75	15.00	6.25	30.00	20.38	10.00	8.50	8.50	5.00	7.00	10
12	12.75	18.00	7.50	36.00	24.38	12.00	10.00	10.00	6.00	8.00	12
14	14.00	21.00	8.75	42.00	28.00	14.00	11.00	11.00	6.50	13.00	14
16	16.00	24.00	10.00	48.00	32.00	16.00	12.00	12.00	7.00	14.00	16
18	18.00	27.00	11.25	54.00	36.00	18.00	13.50	13.50	8.00	15.00	18
20	20.00	30.00	12.50	60.00	40.00	20.00	15.00	15.00	9.00	20.00	20
24	24.00	36.00	15.00	72.00	48.00	24.00	17.00	17.00	10.50	20.00	24

※ 1. Straight Tees

※ 2. Applies for thickness not exceeding "Limiting Wall Thickness"

STEEL BUTTWELDING FITTINGS

DIMENSION OF WELDING FITTINGS

DIMENSION TOLERANCE

ANSI B16.9 & ANSI B16.

Nominal Pipe Size	ALL FITTINGS			90°, 45° TEES	REDUCER	180° RETURNS			CAPS
	O.D. at Bevel	I.D. at End	Wall Thickness	Center to End	Overall Length	Center to Center	Back to Face	Alignments of Ends	Overall Length
1/2 – 2-1/2	+0.06 –0.03	±0.03	Not Less Than 87.5 Percent of Nominal Thickness	±0.06	±0.06	±0.25	±0.25	±0.03	±0.12
3 – 4	±0.06	±0.06							
5 – 8	+0.09 –0.06								
10 – 18	+0.16 –0.12	±0.12		±0.09	±0.09	±0.38		±0.06	±0.25
20 – 24	+0.25 –0.19	±0.19							

STEEL BUTTWELDING FITTINGS

DIMENSION OF WELDING FITTINGS

ANSI B36.10

in inches

Nominal Pipe Size	Outside Dia.	Nominal Wall Thickness					
		Std. Wall	Sch. 40	Extra Strong	Sch. 80	Sch. 160	XX. Strong
1/2	0.84	0.109	0.109	0.147	0.147	0.188	0.294
3/4	1.05	0.113	0.113	0.154	0.154	0.219	0.308
1	1.315	0.133	0.133	0.179	0.179	0.250	0.358
1-1/4	1.660	0.140	0.140	0.191	0.191	0.250	0.382
1-1/2	1.900	0.145	0.145	0.200	0.200	0.281	0.400
2	2.375	0.154	0.154	0.218	0.218	0.343	0.436
2-1/2	2.875	0.203	0.203	0.276	0.270	0.375	0.552
3	3.500	0.216	0.216	0.300	0.300	0.438	0.600
3-1/2	4.000	0.226	0.226	0.318	0.318	0.500	0.636
4	4.500	0.237	0.237	0.337	0.337	0.531	0.674
5	5.563	0.258	0.258	0.375	0.375	0.625	0.750
6	6.625	0.280	0.280	0.432	0.432	0.718	0.864
8	8.625	0.322	0.322	0.500	0.500	0.906	0.875
10	10.750	0.365	0.365	0.500	0.593	1.125	1.000
12	12.750	0.375	0.406	0.500	0.687	1.312	1.000
14	14.000	0.375	0.438	0.500	0.750	1.406	—
16	16.000	0.375	0.500	0.500	0.843	1.593	—
18	18.000	0.375	0.562	0.500	0.937	1.781	—
20	20.000	0.375	0.593	0.500	1.031	1.968	—
24	24.000	0.375	0.687	0.500	1.218	—	—

STEEL BUTTWELDING FITTINGS

DIMENSION OF WELDING FITTINGS

ANSI B36.10

in mm

Nominal Pipe Size	Outside Dia.	Nominal Wall Thickness					
		Std. Wall	Sch. 40	Extra Strong	Sch. 80	Sch. 160	XX. Strong
1/2	21.3	2.77	2.77	3.73	3.73	4.78	7.47
3/4	26.7	2.87	2.87	3.91	3.91	5.56	7.82
1	33.40	3.38	3.38	4.55	4.55	6.35	9.09
1-1/4	42.16	3.56	3.56	4.85	4.85	6.35	9.70
1-1/2	48.26	3.68	3.68	5.08	5.08	7.14	10.16
2	60.32	3.91	3.91	5.54	5.54	8.74	11.07
2-1/2	73.02	5.16	5.16	7.01	7.01	9.52	14.02
3	88.90	5.49	5.49	7.62	7.62	11.13	15.24
3-1/2	101.60	5.74	5.74	8.08	8.08	12.70	16.15
4	114.30	6.02	6.02	8.56	8.56	13.49	17.12
5	141.30	6.55	6.55	9.52	9.52	15.87	19.05
6	168.27	7.11	7.11	10.97	10.97	18.24	21.95
8	219.07	8.18	8.18	12.70	12.70	23.01	22.22
10	273.05	9.27	9.27	12.70	15.06	28.57	25.40
12	323.85	9.52	10.31	12.70	17.45	33.32	25.40
14	355.60	9.52	11.12	12.70	19.05	35.71	—
16	406.40	9.52	12.70	12.70	21.41	40.46	—
18	457.20	9.52	14.27	12.70	23.80	45.24	—
20	508.00	9.52	15.06	12.70	26.19	49.99	—
24	609.60	9.52	17.45	12.70	30.94	—	—

STEEL BUTTWELDING FITTINGS

WEIGHT

in kg

Nominal Pipe Size	Elbows (Long Radius)								
	STD			S40			S80		
	90°	STD 45°	STD 180°	S40 90°	S40 45°	S40 180°	S80 90°	S80 45°	S80 180°
1/2	0.076	0.038	0.152	0.076	0.038	0.152	0.097	0.048	0.194
3/4	0.075	0.036	0.150	0.075	0.036	0.150	0.098	0.047	0.196
1	0.150	0.106	0.300	0.150	0.106	0.300	0.194	0.137	0.388
1-1/4	0.254	0.163	0.508	0.254	0.163	0.508	0.335	0.215	0.670
1-1/2	0.364	0.218	0.728	0.364	0.218	0.728	0.486	0.292	0.972
2	0.651	0.361	1.30	0.651	0.361	1.30	0.895	0.497	1.79
2-1/2	1.29	0.728	2.58	1.29	0.728	2.58	1.71	0.961	3.42
3	2.03	1.09	4.06	2.03	1.09	4.06	2.74	1.47	5.48
3-1/2	2.84	1.47	5.68	2.84	1.47	5.68	3.90	2.02	7.80
4	3.85	1.94	7.70	3.85	1.94	7.70	5.34	2.69	10.7
5	6.51	3.27	13.0	6.51	3.27	13.0	9.26	4.65	18.5
6	10.1	5.10	20.2	10.1	5.10	20.2	15.3	7.69	30.6
8	20.4	10.2	40.8	20.4	10.2	40.8	30.9	15.6	61.8
10	36.1	18.1	72.2	36.1	18.1	72.2	57.3	28.8	114.
12	53.0	26.7	106.	57.2	28.8	107	94.7	47.6	189.
14	68.1	34.2	136.	79.1	39.8	158	132.	66.6	264.
16	89.2	44.9	178.	118.	59.4	236	195.	97.9	390.
18	113.	56.9	226.	168.	84.5	336	274.	138.	548.
20	140.	70.5	280.	219.	110.	438	372.	187.	744.
24	202.	102.	404.	36.6	184.	732	634.	319.	—

STEEL BUTTWELDING FITTINGS

WEIGHT

in kg

Nominal Pipe Size	Elbows (Short Radius)			Tees		Reducers		Caps	
	STD	S40	S80	STD	XS	STD	XS	STD	XS
	90°	90°	90°						
1/2	–	–	–	0.085	0.107	–	–	0.036	0.044
3/4	–	–	–	0.125	0.162	0.059	0.075	0.049	0.062
1	0.100	0.100	0.129	0.250	0.318	0.116	0.147	0.109	0.144
1-1/4	0.169	0.169	0.223	0.421	0.554	0.157	0.206	0.145	0.197
1-1/2	0.242	0.242	0.324	0.603	0.805	0.243	0.324	0.171	0.236
2	0.434	0.434	0.597	0.872	1.19	0.372	0.508	0.234	0.330
2-1/2	0.861	0.864	1.14	1.74	2.28	0.723	0.945	0.420	0.565
3	1.35	1.35	1.83	2.41	3.25	0.933	1.25	0.664	0.917
3-1/2	1.89	1.87	2.60	3.17	4.39	1.28	1.77	0.958	1.36
4	2.57	2.57	3.56	4.12	5.76	1.53	2.14	1.17	1.68
5	4.34	4.85	6.17	6.53	9.20	2.50	3.51	1.90	2.73
6	6.77	6.77	10.2	9.58	14.5	3.57	5.38	2.83	4.38
8	13.6	14.5	20.6	17.9	27.1	5.70	8.61	5.11	7.91
10	24.1	25.4	38.2	30.4	41.0	9.58	12.9	8.92	12.2
12	35.3	38.2	63.1	43.6	57.7	13.6	18.0	13.0	17.4
14	45.4	52.8	88.3	53.5	70.9	25.4	33.6	15.9	21.2
16	59.5	78.7	130.	66.1	87.7	31.0	41.1	20.0	26.7
18	75.5	112.	183.	83.9	111.	37.8	50.1	25.5	34.1
20	93.4	146.	248.	104.	138.	56.4	74.9	31.8	42.5
24	135.	244.	423	139.	185	65.7	87.1	44.5	60.1



**ELBOW
(90° OR 45°)
LR/SR**



**TEE
REDUCER**



**TEE OR
TEE EQUAL**



**ECCENTRIC
REDUCER**



**CONCENTRIC
REDUCER**

SPECIFICATIONS:

STANDARDS:

ASTM A105 , API, ASME, AND ANSI B16.5

- size: 1/4" - 48"
- Thickness: Class 150-2,500
- All Items will have an accompanying Mill Test Certificate upon request

APPLICATIONS:

- Industrial
- Residential
- Petrochemical Plants
- Oil & Gas
- Refineries
- Sugar Mills
- Energy
- Construction & Infrastructure
- Chemicals
- Machineries
- Boilers
- Food & Beverage
- Shipping
- Desalination Plant
- Machineries
- Automotive & Transport
- High-Pressure Vessel
- Power Plants

WHY CHOOSE US?

1 RELIABLE

Since 1961, We have been a trusted vendor for some of the Philippines' biggest companies across sectors in Oil Refinery, Petroleum, Geothermal, LNG, LPG, Power/Energy, Chemical, Sugar Mill, Food/Beverage, Distillery & International Sub-Contractors.

2 COMPETITIVE PRICING

As a Direct Importer, Wholesaler, Retailer, Stockist, and Exclusive Agent, we can offer our clients the most competitive of prices in an ever changing market.

3 QUALITY PRODUCTS

We carry a wide range of materials that conforms to various International Standards such as ASME, ANSI, WRAS, BSI, and ULFM.



OKI[®]